# Osprey Elite



# The ${\it Elit}$ is the most versatile of the Osprey range designed to support the latest range of digital, portable and full facility cameras for both studio and OB productions.

The two-stage column offers 'on-shot' movement from a minimum height of 26 " / 66 cm to a high of 56 " / 143 cm with full crab and steer facilities controlled from a central steering ring.

The *Elit* has an exceptional combination of lightness and structural integrity giving maximum stability while still allowing the column and dolly base to fold for easy transportation. Optional accessories include a portable hand pump to counterbalance the pneumatic system.

### **Optional Accessories**

<i>3357-3</i>	Portable Pump
3329-30	OB Wheel Set for Ospreys (set of 3)
3329-21	Osprey Tiller
3429-21	Large Steering Ring 24.8 " / 63.5 cm
3369-50 J	
3369-56	Tracking Skid for Osprey Columns
3369-57 <sup>J</sup>	
3329-44	OB Wheel Cable Guards (set of 3)



#### > Lightweight Construction

- > Extensive 'On-Shot' Capability
- > Low Pressure Counterbalance System
- > Removable Steering Ring and Kick Ring

Specification:

Model No: 3574-3C Elite Studio pedestal (Black)

Capacity: 165 lbs / 75 kg (Maximum capacity includes trim weights)

Minimum Height: 26 " / 66 cm

Maximum Height: 56 " / 143 cm

'On-Shot' Stroke: 30.3 " / 77 cm

Wheel Lock: Yes

Weight: 101 lbs / 45.7 kg
Doorway Tracking Width: 38.2 " / 97 cm
Transit Doorway Width: 31.5 " / 80 cm
Narrow Doorway Width: 28.5 " / 72.3 cm
Wheel Diameter: 5 " / 12.5 cm

**Detachable Steering** 

Ring Diameter: 21 " / 53.3 cm Trim weights: 7.5 lbs / 3.4 kg

Ground clearance: 0.78"

### **Model No: 3574-3B Elite OB pedestal (Black)** (As Studio Version except for)

 Minimum Height:
 27 " / 68.5 cm

 Maximum Height:
 57.3 " / 145.5 cm

 Weight:
 107.4 lbs / 48.7 kg

 Wheel Diameter:
 6.3 " / 16 cm

 Ground Clearance:
 1.2 " / 3.45 cm



simply and easily transportable